



Husky

By Sweeprite



**COVER
MORE
GROUND.**

DESIGNED TO PERFORM. BUILT TO LAST.




The Husky is a 4-wheel mechanical broom sweeper that through innovative engineering, provides:

- Outstanding sweeping performance, simplicity and reliability.
- A high level of driver comfort, safety and visibility.
- An investment that dollar-for-dollar spent, outperforms the competition.

Sweeprite's patented* sweeping technology gives you excellent sweeping performance in a wide range of applications and conditions.

The Sweeprite System means more debris from the surface goes into the hopper. -Trash, sand, gravel, dirt and millings, construction site clean-up and more.

The result? A fully functional broom sweeper capable of tough sweeping jobs that maximizes productivity while keeping your up-front investment low and operating costs down.



Floating, adjustable
Gutter Brooms.
With Patented*
Water Saver System.



POWERFUL SWEEPING
REVOLUTIONARY
WATER SAVING
DURABLE SQUEEZING
FREE-FLOATING
HIGH AND LOW
CENTER MOUNTED
LOW OPERATING
COMPACT TRUCK
VISIBILITY &

Sweeprite

COVER MORE GROUND



10

Reasons To Own a Husky:

1. Powerful Sweep System:

The Husky uses proven and dependable tandem gear pumps to hydraulically drive the main and gutter brooms, elevator and hopper dump. Easy to operate. Simple to maintain.

2. Revolutionary Main Broom:

"The Eliminator", Sweeprite's patented* 58" main broom picks up where others won't. This industry-first broom design uses angled-forward leading edges to virtually eliminate streaking. You will pick up more debris, dirt and trash.

3. Sweeprite's patented* "Water Saver":

Our system puts water at the tip of the gutter broom bristles. This keeps dust to a minimum and uses less water than other systems.

4. Durable Squeegee-type elevator:

Puts more debris into the hopper quickly and efficiently with less maintenance.

5. Free-floating, fully adjustable gutter brooms:

Follow the contour of the road surface. All brooms are independently driven for maximum reserve sweeping torque and increased operating flexibility.

6. High dump and low dump options:

Dependable scissor-type lift mechanism enables infinite variable height dumping from 24" ground dump to full 9 feet. Lets you dump debris where you want, when you want.

7. Centre Debris Hopper:

Centre mounted hopper provides even load distribution, clear view of hopper via lexan windows and a full 4 cubic yard volumetric capacity.

8. Low overall operating and maintenance costs:

Simplicity of design, innovative engineering and quality craftsmanship produce sweepers that spend more time on the road sweeping.

9. Small, nimble truck chassis:

Enables extreme maneuverability and fast travel between sweeping jobs.

10. Excellent operator visibility and comfort:

The standard truck chassis offers outstanding visibility, ride, short 109" wheelbase and tight maneuverability. Components are easily accessible for fast & easy service.

*Patents pending



Revolutionary
"Eliminator" Main Broom.
Pick up more debris.
Cover more ground.



SWEEP SYSTEM
MAIN BROOM
* SYSTEM
EGEE ELEVATOR
NG BROOMS
W DUMPING
ITED HOPPER
TING COSTS
CK CHASSIS
COMFORT

Sweeprite

HUSKY BY SWEEPRITE

HUSKY SPECIFICATIONS

General:

Sweeping path:	112" maximum
Overall height:	92"
Hopper capacity:	4 cubic yards volumetric
Dump height max:	9 ft.
Dump location:	Left side standard
Chassis:	GMC W4500 / ISUZU NPR Cab-over
Wheelbase:	109"
GVWR:	14,500 lbs./6,577 kg

Gutter Brooms:

Number of brooms:	2
Diameter:	32"
Number of segments:	4
Hydraulic direct drive:	Reversible
Adjustment:	Independent, left, right, up & down
Controls:	Pressure & wear
Design:	Free-floating spring suspension

Engine, Auxiliary:

Manufacturer:	Kubota
Model:	V2003T, 4 cylinder Turbo Diesel
Displacement:	1999 C.C.
Rated horsepower:	56 hp @ 2800 rpm
Torque:	120 ft-lbs @ 2000 rpm

Auxiliary Engine/Sweeper Instrumentation:

Tachometer and Hour meter
Engine oil pressure warning light
Engine coolant temperature light

Truck Specifications:

Manufacturer:	GMC / ISUZU
Model:	W4500 / NPR
Design:	Cab-over
Engine:	Isuzu 4HE 1XS, 290 cu. in. Turbo Diesel
Horsepower:	175 hp @ 2700 rpm
Torque:	347 ft-lb. @ 2000 rpm
Transmission:	Automatic, 4 speed
Steering:	Power w/tilt & telescoping column
Axles:	Front: 6,830 lbs. / Rear: 11,020 lbs.
Brakes:	Hydraulic, front discs rear drum

Conveyor:

Squeegee-type system.
Hydraulic direct drive, reversible
relief valve protected.

Main Broom:

"The Eliminator" Patent pending.
Steel core: 10" dia. x 58" long.
Hydraulic direct drive, reversible.
Filled diameter, 32"

Debris Hopper:

Material volume:	4.0 cubic yards volumetric
Maximum dump height:	9 feet
Minimum dump height:	24"
Left dumping:	Standard
Dump capacity:	6,000 lbs./2,722 kg

Water System:

"Water Saver" Patent pending	
Capacity:	140 Gallons US
Tank Material:	Polyethylene
Electric pump (1):	Diaphragm, 3.0 gpm
Water system material:	All plastic, non-corrosive

Hydraulic System:

Tank capacity:	45 gallons
Pump:	Dual Tandem gear
Pump capacity:	10 gpm/10 gpm
Controls:	Electric over hydraulic
Hydraulic drive motors:	All interchangeable
Hydraulic fluid cooler:	Air to oil

Lighting System:

2 Halogen headlamps, rectangular.
2 Stop/tail lights.
2 turn signal lights, front and rear.
Cab marker lights and rear clearance lights.
Warning beacon & emergency flasher lights.
Back-up lights, automatic with audible alarm.
License plate light.

Wheels & Tires:

215 85R16E, 10 ply radials, Duals on rear axle.

Options:

GVWR: 17950 lbs./8,142 kg
Hydraulic fluid temperature light
Hydraulic fluid low-level warning light
Hydraulic filter warning light
Squeegee-type system, stainless steel floor pan.

For a complete list of specifications and options available, please contact factory or your nearest dealer.

Sweeprite Mfg. Inc.

Box 3344, 1891 Albert Street N.

Regina, SK Canada S4P 3H1

Telephone: (306) 543-2020 / Fax: (306) 775-0447

Toll Free: 888-446-4494

Website: www.sweeprite.com email: sales@sweeprite.com