

TALBERT

Traveling Axle Trailers



6 DEGREE LOAD
ANGLE

28 DEGREE DUMP
ANGLE



35 TON & 50 TON CAPACITY



Triple reinforced approach plate lies flat with maximum ground bearing area to help protect pavement during loading and unloading of equipment **(Standard)**



Suspension straps are mounted on the shocks to prevent over extension of the air ride suspension **(Standard)**



Dock loading capabilities - 62,000 lbs. Levelers **(Optional)**

SPECIFICATIONS AND STANDARD FEATURES

MODEL	SSTA3548
CAPACITY	70,000 LBS. DISTRIBUTED IN 48'-0" 50,000 LBS. CONCENTRATED IN 10'-0"
FRAME	T1 & 80 KSI 4 BEAM CONSTRUCTION
LOAD ANGLE	6 DEGREE (28 DEGREE DUMP ANGLE)
LENGTH	48'-0" OVERALL
LOADSPACE	10'-8" UPPER DECK, 37'-4" LOWER DECK
WIDTH	8'-6"
POWER SOURCE	PTO OPERATION
SWING RADIUS	86" (18" SETTING)
FIFTH WHEEL HT.	48" LOADED
FLOOR	1 5/16" APITONG WITH SCREWS
WINCH	15,000 LBS. PLANETARY HYDRAULIC WITH AIR CLUTCH, 100' OF 1/2" CABLE W/TENSIONER ROLLER GUIDE, 18" ROLLER GUIDE IN LOWER DECK
REMOTE	DUAL REMOTE CONTROL
FOR WINCH	
LANDING GEAR	2 SPEED LANDING GEAR
TOOL BOX	LARGE LOCKABLE UNDER GOOSENECK
CROSSMEMBERS	4" JR 1 - BEAM ON 9" CENTERS (FORK LIFT PACKAGE)
TIE DOWNS	DOUBLE KEY HOLE CHAIN SLOTS IN CENTER OF DECK, 6 CHAIN HOLES ACROSS REAR APPROACH PLATE
DECK HT.	38" LOADED
BRAKES	12 1/4" X 7 1/2" AIR WITH AUTO SLACKS
ABS	2S IM SYSTEM
WHEELS	6.75 X 17.5 8 HOLE HUB PILOTED WITH OIL WHEEL SEALS
TIRES	235/75R17.5 16 PR RADIAL
SUSPENSION	RIDEWELL AIR
APPROACH PLATE	TRIPLE REINFORCED STEEL PLATE
MUD FLAPS	ANTI SAIL
LIGHTS	7 WAY PLUG WITH L.E.D. LIGHTS
TRIM	CONSPICUITY TAPE
FINISH	STANDARD RED ENAMEL
WEIGHT	17,300 LBS. (+/- 5%)

**ALL SPECIFICATIONS ARE
SUBJECT TO CHANGE WITH-
OUT NOTICE**

**Telephone Numbers:
800-348-5232
219-866-7141**



Cable roller in lower deck section for efficient loading with the winch **(Standard)**

Available Options

- 53'-0" LENGTH
- DOCK LEVELERS (62,000 LBS.)
- HYDRAULIC LANDING GEAR
- GAS ENGINE POWER PACKAGE
- FLIP UP RAMPS - UPPER DECK
- 20,000 LBS. WINCH
- 4,6,8, OR 10 FUNCTION REMOTE CONTROL
- 1/8" STEEL TREADPLATE ILO APITONG
- HUBODOMETER
- FLUSH MOUNTED "D" RINGS
- BULKHEADS (STEEL OR ALUMINUM)
- SWING - OUT OUTRIGGERS
- ALUMINUM WHEELS
- 3 TAIL LIGHT PACKAGE
- ELECTRICAL PLUG AT REAR FOR BEACON
- MALE 4 WAY PLUG AT REAR
- ALUMINUM DRESS PACKAGE
- AIR WEIGH COMLINK SYSTEM
- 1/8" OR 3/16" METAL ON REAR OF DECK



Smooth transition from lower deck to upper deck for easier and safer loading **(Standard)** Heavy duty stainless steel hinges and latch, the most durable in the industry. **(Standard)**

Self - contained power package on a slide out tray provides easy access for service **(Optional)**



Planetary 15,000 lbs. hydraulic winch with air clutch, 100'-0" 1/2" cable w/ roller guide; tensioners & dual function wireless remote control for winch **(Standard)**

Two speed landing gear **(Standard)**



Visit us at our web site www.talbertmfg.com and try out our free to use weight distribution program for your truck and trailer