

# WASHEX WASHER / EXTRACTOR PRODUCT LINE

Washex, Inc. is one of the world's leading manufacturers of washer/extractors; microcontamination; and denim processing machines. An international company, Washex produces a broad spectrum of machine models and options, and is supported by a worldwide sales, distribution, and service network.

## END-LOADING NON-TILTING

### CAPACITY RANGE: 85 – 90 lbs. (40 – 41 kg)



- RVS 350** – 85 lb. (40 kg)
- Rigid mount
  - Single motor drive
  - New Elite<sup>II</sup> microprocessor
  - Programmable variable speed wash and extract
  - Dry Zone Bearing (DZB)<sup>TM</sup>



- FVS 450** – 90 lb (41 kg)
- Floataire<sup>®</sup> suspension system
  - Single motor drive
  - New Elite<sup>II</sup> microprocessor
  - Programmable variable speed wash and extract
  - Dry Zone Bearing (DZB)<sup>TM</sup>



- RVS 550** – 125 lb (60 kg)
- Rigid mount
  - Single motor drive
  - New Elite<sup>II</sup> microprocessor
  - Programmable variable speed wash and extract
  - Dry Zone Bearing (DZB)<sup>TM</sup>

### CAPACITY RANGE: 125 lbs. (60 kg)

### CAPACITY RANGE: 135 lbs. (65 kg)

**FVS 600** – 135 lb (65 kg)



- Floataire<sup>®</sup> suspension system
- Single motor drive
- New Elite<sup>II</sup> microprocessor
- Programmable variable speed wash and extract
- Dry Zone Bearing (DZB)<sup>TM</sup>

### CAPACITY RANGE: 175 lbs. (80 kg)

**FVS 800** – 175 lb (80 kg)



- Floataire<sup>®</sup> suspension
- Single motor drive
- New Elite<sup>II</sup> microprocessor
- Programmable variable speed wash and extract
- Dry Zone Bearing (DZB)<sup>TM</sup>

### CAPACITY RANGE: 250 – 275 lbs. (125 kg)



- FVS 1200**  
275 lb (125 kg)
- Floataire<sup>®</sup> Suspension
  - Single motor drive
  - New Elite<sup>II</sup> microprocessor
  - Dry Zone Bearing (DZB)<sup>TM</sup>
  - Quick Seal Replacement (QSR)<sup>TM</sup> technology

## END-LOADING TILTING

### CAPACITY RANGE: 275 lbs. (125 kg)



- FLPS 1200** – 275 lb (125 kg)
- Floataire<sup>®</sup> Suspension system
  - Single motor drive
  - New, Elite advanced, microprocessor
  - Two way tilt
  - Dry Zone Bearing (DZB)<sup>TM</sup> design
  - Quick Seal Replacement (QSR)<sup>TM</sup> technology

### CAPACITY RANGE: 450 lbs. (200kg)



- FLPS 2250**  
450 lb (200 kg)
- Floataire<sup>®</sup> Suspension
  - New Elite microprocessor
  - Two way tilt
  - Single motor drive

### CAPACITY RANGE: 550 lbs. (250 kg)

**FLPS 2500** – 550 lb (250 kg)



- Floataire<sup>®</sup> Suspension system
- Two way tilt
- Single motor variable speed drive
- Programmable variable speed wash and extract
- Optima Elite microprocessor
- Dry Zone Bearing (DZB)<sup>TM</sup> design
- Quick Seal Replacement (QSR)<sup>TM</sup>

### DENIM PROCESSING SYSTEMS – CAPACITY RANGE: 800 – 1000 lbs.

**DTF 4000** 4000 liters (141 cu. ft.)  
**DTF 5000** 5000 liters (176 cu. ft.)



- Pneumatic 18' unload tilt
- Rigid mount
- Multi-motor drive
- Optima microprocessor
- Dry Zone Bearing (DZB)<sup>TM</sup>
- Quick Seal Replacement (QSR)<sup>TM</sup>



- DPM 4000** 4000 liters (141 cu. ft.)  
**DPM 5000** 5000 liters (176 cu. ft.)
- Hydraulic 30' unload tilt
  - Hydraulic 25' load tilt
  - Rigid mount construction
  - Single motor drive
  - Programmable variable speed wash and extract
  - Optima Elite microprocessor
  - Removable cylinder inserts
  - Dry Zone Bearing (DZB)<sup>TM</sup>
  - Quick Seal Replacement (QSR)<sup>TM</sup> technology

## PASS-THROUGH

### PASS-THROUGH WASHER / EXTRACTORS – CAPACITY RANGE: 80 – 700 lbs. (36 kg - 320 kg.)

**WX 300 SERIES and ANTI CROSS CONTAMINATION (ACC) SERIES**

- 2-Pocket Cylinder
- 3-Pocket Option for WX 312 & 320
- Designed For Barrier Wall Installation



**WX 308**  
80 lb (36 kg)




**WX 312**  
120 lb (55 kg)




**WX 320**  
200 lb (91 kg)




**ACC 1100**  
240 lb (110 kg)



**ACC 1600**  
350 lb (160 kg)



**ACC 2100**  
480 lb (220 kg)



**ACC 3000**  
700 lb (320 kg)

- Automatic Supply Dispenser with Automatic Flush
- Air Cushion & Gas Shock Absorber Suspension Sys.
- Microprocessor Control with 99 Formula Capability
- Single Motor with Variable Speed Inverter Drive

## NON-PASS-THROUGH

### PASS-THROUGH SIDE-LOADING WASHER / EXTRACTORS – CAPACITY RANGE: 240 - 700 lbs. (110 - 320 kg)

- **FLA 1100** 240 lb (110 kg)
- **FLA 1600** 350 lb (160 kg)
- **FLA 2100** 480 lb (220 kg)
- **FLA 3000** 700 lb (320 kg)

Suitable for any type of laundry operation, Washex side-loaders are quality engineered and built tough as a tank, outlasting other washer/extractors while providing predictable, durable performance. For greater productivity, these models are especially suited for labor-saving overhead chute or sling loading systems.



## DUMPING SIDE-LOADING

### TILTING SIDE-LOADING WASHER / EXTRACTORS – CAPACITY RANGE: 900 lbs. (410 kg)



**DSL 4500**  
900 lb (410 kg)

► **Features numerous operational innovations!**



- Four large diameter Open Pockets
- Exclusive Dry Zone Bearing and Quick Seal Replacement technologies
- High angle hydraulic Tilt for unloading
- Easy-to-use process controller
- Washex Floataire Suspension System