





INTERIOR and EXTERIOR STOCK COLORS


Polar Bear White



Navajo White



Linen White



Bone White



Buckskin




Sahara Sand



Dunnes Tan



Deep Sea



Concrete



Driftwood



Pewter



Shadow



All paints are formulated to match the color chips as accurately as possible; however, variations in the type of product, gloss, texture, lighting and adjacent colors can cause a difference in appearance between the color of the chip and the color of the applied paint.

QUALITY LATEX PAINT

Interior / Exterior Paint

- Flat Finish
- Eggshell Enamel
- Semi-Gloss

Excellent adhesion, affordable latex paint products can be brushed, rolled or sprayed.

- Durable
- Low Odor
- Custom Colors
- Water Clean-Up
- Easy Application
- Broad Range of Colors
- Consistent Color Matching

Paint products produced by VRI, Inc™.

To Reorder Contact

4205 South Market Ct.
Sacramento, CA 95834
800-770-7664 Toll Free
916-564-9121 Business Office
916-568-1485 Fax



4205 South Market Ct.
Sacramento, CA 95834

100 Interior/Exterior Latex Flat Finish

CHARACTERISTICS:

- Excellent Quality
- Interior/Exterior Latex Flat Finish
- Excellent Adhesion
- Weather Resistant
- Durable
- Easy Application
- Water Clean-Up
- Low Odor

PHYSICAL PROPERTIES:

Finish:
Sheen @ 60° ----- 2-6%

COLORS:

Available in many interior/exterior stock colors. Custom colors available on request.

VISCOSITY:

Package KU Viscosity 100-110KU

PERFORMANCE PROPERTIES:

Approximately 200-500 sq. ft. per gallon depending on substrate and application method, porosity and surface texture.

* Approximate coverage for each coat.

DRYING TIME:

To Touch ----- 30-60 minutes
To Recoat ----- 5-6 hours
Cure ----- 7 days

PREPARATION & PRIMING

BLOCK:

Allow new block to cure before application of primers and finish coats. Remove loose mortar and patch all voids with appropriate patching or caulking material. Clean surface to remove dirt, efflorescence, grease, oil, wax, mildew or other foreign matter.

CONCRETE:

Allow new concrete to cure for 60 days before application of primer and finish coats.

Patch all voids with the appropriate patching or caulking material. Power wash all tilt-up and poured in place concrete to remove any bond-breakers or other construction residue. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material.

METAL:

Apply finish to primed or previously painted metal with no visible rust. Scrape, power tool clean and sand the surface to remove any dirt, grease, oil, rust, scale, loose shop prime or other foreign matter.

STUCCO:

Allow new stucco to cure before application of finish coats. Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material. Best results are obtained when surface is back rolled.

WOOD:

Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, grease, oil, wax, mildew or other foreign matter.

PREVIOUSLY PAINTED SURFACES:

Patch all voids with the appropriate patching or caulking material. Wash, scrape, sand and clean the surface to remove any chalk, dirt, grease, oil, wax, mildew, loose paint or other foreign material.

APPLICATION

METHODS:

May be applied with brush, roller or airless sprayer. Maintain a "wet edge" and apply coating uniformly.

THINNING:

Product intended for used at package consistency. If thinning is desired, do not thin more than 1/2 pint per gallon.

CLEAN-UP:

Clean up equipment and area with warm soapy water.

APPLICATION:

Do not apply where material, air or surface temperature is below 50° F. Surfaces and ambient temperatures must be between 48° F. and 100° F., 5° above dewpoint and remain above 48° F. for a minimum of four hours after application.

All paint products should be tested for adhesion, appearance, color and compatibility prior to application.

PERSONAL:

Paint may be irritating to eyes, nose and skin. Avoid contact with eyes. In case of eye contact, flush at least fifteen minutes and call a physician immediately.

STORAGE:

KEEP FROM FREEZING
STORE ABOVE 50° F
MAXIMUM VOC: 250 G/L

CAUTION

Avoid contact with eyes, skin and clothing.
Do not take internally.
Wash thoroughly after handling. Close container after each use. For additional information consult the Material Safety Data Sheet (MSDS).

KEEP OUT OF REACH OF CHILDREN.
USE ONLY WITH ADEQUATE VENTILATION.



4205 South Market Ct.
Sacramento, CA 95834

200 Interior/Exterior Latex Eggshell Finish

CHARACTERISTICS:

- Excellent Quality
- Interior/Exterior Latex Flat Finish
- Excellent Adhesion
- Weather Resistant
- Durable
- Easy Application
- Water Clean-Up
- Low Odor

PHYSICAL PROPERTIES:

Finish:
Sheen @ 60° ----- 7-14%

COLORS:

Available in many interior/exterior stock colors. Customs colors available on request.

VISCOSITY:

Package KU Viscosity 90-100KU

PERFORMANCE PROPERTIES:

Approximately 200-500 sq. ft. per gallon depending on substrate and application method, porosity and surface texture.

* Approximate coverage for each coat.

DRYING TIME:

To Touch ----- 30-60 minutes
To Recoat ----- 5-6 hours
Cure ----- 7 days

PREPARTION & PRIMING

BLOCK:

Allow new block to cure before application of primers and finish coats. Remove loose mortar and patch all voids with appropriate patching or caulking material. Clean surface to remove dirt, efflorescence, grease, oil, wax, mildew or other foreign matter.

CONCRETE:

Allow new concrete to cure for 60 days before application of primer and finish coats.

Patch all voids with the appropriate patching or caulking material. Power wash all tilt-up and poured in place concrete to remove any bond-breakers or other construction residue. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material.

METAL:

Apply finish to primed or previously painted metal with no visible rust. Scrape, power tool clean and sand the surface to remove any dirt, grease, oil, rust, scale, loose shop prime or other foreign matter.

STUCCO:

Allow new stucco to cure before application of finish coats. Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material. Best results are obtained when surface is back rolled.

WOOD:

Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, grease, oil, wax, mildew or other foreign matter.

PREVIOUSLY PAINTED SURFACES:

Patch all voids with the appropriate patching or caulking material. Wash, scrape, sand and clean the surface to remove any chalk, dirt, grease, oil, wax, mildew, loose paint or other foreign material.

APPLICATION

METHODS:

May be applied with brush, roller or airless sprayer. Maintain a "wet edge" and apply coating uniformly.

THINNING:

Product intended for used at package consistency. If thinning is desired, do not thin more than 1/2 pint per gallon.

CLEAN-UP:

Clean up equipment and area with warm soapy water.

APPLICATION:

Do not apply where material, air or surface temperature is below 50° F. Surfaces and ambient temperatures must be between 48° F. and 100° F., 5° above dewpoint and remain above 48° F. for a minimum of four hours after application.

All paint products should be tested for adhesion, appearance, color and compatibility prior to application.

PERSONAL:

Paint may be irritating to eyes, nose and skin. Avoid contact with eyes. In case of eye contact, flush at least fifteen minutes and call a physician immediately.

STORAGE:

KEEP FROM FREEZING
STORE ABOVE 50° F
MAXIMUM VOC: 250 G/L

CAUTION

Avoid contact with eyes, skin and clothing.
Do not take internally.
Wash thoroughly after handling. Close container after each use. For additional information consult the Material Safety Data Sheet (MSDS).

KEEP OUT OF REACH OF CHILDREN.
USE ONLY WITH ADEQUATE VENTILATION.



4205 South Market Ct.
Sacramento, CA 95834

300 Interior/Exterior Latex Semi-Gloss

CHARACTERISTICS:

- Excellent Quality
- Interior/Exterior Latex Flat Finish
- Excellent Adhesion
- Weather Resistant
- Durable
- Easy Application
- Water Clean-Up
- Low Odor

PHYSICAL PROPERTIES:

Finish:
Sheen @ 60° ----- 15-25%

COLORS:

Available in many interior/exterior stock colors. Customs colors available on request.

VISCOSITY:

Package KU Viscosity 90-100KU

PERFORMANCE PROPERTIES:

Approximately 200-500 sq. ft. per gallon depending on substrate and application method, porosity and surface texture.

* Approximate coverage for each coat.

DRYING TIME:

To Touch ----- 30-60 minutes
To Recoat ----- 5-6 hours
Cure ----- 7 days

PREPARATION & PRIMING

BLOCK:

Allow new block to cure before application of primers and finish coats. Remove loose mortar and patch all voids with appropriate patching or caulking material. Clean surface to remove dirt, efflorescence, grease, oil, wax, mildew or other foreign matter.

CONCRETE:

Allow new concrete to cure for 60 days before application of primer and finish coats.

Patch all voids with the appropriate patching or caulking material. Power wash all tilt-up and poured in place concrete to remove any bond-breakers or other construction residue. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material.

METAL:

Apply finish to primed or previously painted metal with no visible rust. Scrape, power tool clean and sand the surface to remove any dirt, grease, oil, rust, scale, loose shop prime or other foreign matter.

STUCCO:

Allow new stucco to cure before application of finish coats. Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, efflorescence, grease, oil, wax, mildew or other foreign material. Best results are obtained when surface is back rolled.

WOOD:

Patch all voids with the appropriate patching or caulking material. Clean the surface to remove any dirt, grease, oil, wax, mildew or other foreign matter.

PREVIOUSLY PAINTED SURFACES:

Patch all voids with the appropriate patching or caulking material. Wash, scrape, sand and clean the surface to remove any chalk, dirt, grease, oil, wax, mildew, loose paint or other foreign material.

APPLICATION

METHODS:

May be applied with brush, roller or airless sprayer. Maintain a "wet edge" and apply coating uniformly.

THINNING:

Product intended for used at package consistency. If thinning is desired, do not thin more than 1/2 pint per gallon.

CLEAN-UP:

Clean up equipment and area with warm soapy water.

APPLICATION:

Do not apply where material, air or surface temperature is below 50° F. Surfaces and ambient temperatures must be between 48° F. and 100° F., 5° above dewpoint and remain above 48° F. for a minimum of four hours after application.

All paint products should be tested for adhesion, appearance, color and compatibility prior to application.

PERSONAL:

Paint may be irritating to eyes, nose and skin. Avoid contact with eyes. In case of eye contact, flush at least fifteen minutes and call a physician immediately.

STORAGE:

KEEP FROM FREEZING
STORE ABOVE 50° F
MAXIMUM VOC: 250 G/L

CAUTION

Avoid contact with eyes, skin and clothing.
Do not take internally.
Wash thoroughly after handling. Close container after each use. For additional information consult the Material Safety Data Sheet (MSDS).

KEEP OUT OF REACH OF CHILDREN.
USE ONLY WITH ADEQUATE VENTILATION.

VI – HEALTH HAZARD DATA

SYMPTOMS / EFFECTS OF EXPOSURE AND OVEREXPOSURE

PRIMARY ROUTES OF ENTRY: Inhalation, skin and eye contact, ingestion.

ACUTE: Dizziness, headache, nausea, confusion, irritation to upper respiratory tract, skin & eye irritation.

CHRONIC: None known.

MEDICAL CONDITIONS PRONE TO AGGRAVATION BY EXPOSURE: None known. See your physician for specific medical opinion regarding your condition.

EMERGENCY AND FIRST AID PROCEDURES

INHALATION: Remove to fresh air. Restore breathing. Consult physician.

EYE CONTACT: Flush with large volumes of water for 15 minutes. Get medical attention.

SKIN CONTACT: Wipe off with a rag. Wash thoroughly with soap and water.

INGESTION: Consult hospital emergency room or Poison Control Center immediately.

VII – PRECAUTIONS FOR HANDLING & USE

STEPS TO BE TAKEN IN CASE MATERIAL IS SPILLED: Ventilate area to prevent build-up of vapors. For small spills, soak up with absorbent material. For larger spills, dike area with absorbent material and scoop up liquids.

WASTE DISPOSAL METHOD: Discard in landfill in sealed containers away from heat and flame and in accordance with local regulations.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Store upright in sealed containers away from heat and flame.

OTHER PRECAUTIONS: This product contains pigments which like most naturally occurring minerals contain small amounts of crystalline silica. This presents no hazard when applying the coating, but sanding it will cause a dust hazard.

IARC has determined that if you breath crystalline silica as a dust you could get cancer. The control measures in Section VIII should be followed when you sand this product and most other paints and building materials such as spackles and dry wall compounds.

REMOVE AND WASH CONTAMINATED CLOTHING BEFORE RE-USE.

VIII – CONTROL MEASURES

RESPIRATORY PROTECTION: Use a particle mask (NIOSH/MSHA TC-21C) to avoid breathing spray mist or sanding dust if local ventilation is inadequate to keep concentrations within acceptable (TLV) limits. If local ventilation is not sufficient, or where exposure limits are exceeded, wear a suitable, properly fitted respirator (NIOSH/MSHA TC-23C, or better) for organic vapors with a dust filter as needed.

VENTILATION: Local cross-ventilation or mechanical exhaust sufficient to keep all hazardous concentrations below prescribed limits.

PROTECTIVE GLOVES: Recommended if necessary to prevent extended exposure.

EYE PROTECTION: Glasses with side shields or goggles are recommended to prevent eye contact.

NOTE: THIS INFORMATION IS BELIEVED TO BE COMPLETE AND ACCURATE. IF ANY QUESTIONS ARISE, CONTACT MANUFACTURER LISTED ABOVE.